






















# Rockshaft/Hitch/PTO/Drawbar

	<b>A-70227323</b>	Gear, Intermediate PTO Drive	4.30 Lbs.		
		<b>Dim/Info:</b> 33 / 19 Tooth			
	<b>For Models:</b> WD, WD45				
<b>AGCO</b>					
<b>ALLIS</b>					
<b>CHALMERS</b>					
<b>DEUTZ</b>	<b>A-70224642</b>	Seal, PTO Shifter	0.10 Lbs.		
					
	<b>For Models:</b> WD, WD45				
<b>MASSEY</b>					
<b>FERGUSON</b>					
<b>WHITE/</b>					
<b>OLIVER</b>					
	<b>A-70224528</b>	Shaft, PTO Stub	2.84 Lbs.		
		<b>Dim/Info:</b> 6 Spline 6.560" Long			
	<b>For Models:</b> WD, WD45				
<b>CNH</b>	<b>A-70222663</b>	Shaft, PTO w/ Coupling (540 RPM) Includes Coupling 70218386.	17.15 Lbs.		
		<b>Dim/Info:</b> 6 Spline 41.000" Long			
	<b>For Models:</b> WD, WD45				
<b>CASE-IH</b>					
<b>FORD / NEW</b>					
<b>HOLLAND</b>					
<b>FIAT</b>	<b>A-70231938</b>	Shaft, PTO, Rear (540 RPM) <b>Replaces:</b> 70229312	19.60 Lbs.		
		<b>Dim/Info:</b> 6/6 Splines 41.375" Long 6 / 6 Splines 41.375" Long			
	<b>For Models:</b> D17, 170, 175, 180, 185				
<b>BELARUS</b>					
<b>BOBCAT</b>	<b>A-70255802</b>	Shaft, PTO (540/1000 RPM) NOTE: Center mounting ring is 5.750" dia., w/ 4 bolt holes inner & outer.	8.00 Lbs.		
		<b>Dim/Info:</b> 7.875" Long			
	<b>For Models:</b> 170, 175, 180, 185 SN <12800, 190, 190XT, 200				
<b>JCB</b>					
<b>JOHN</b>					
<b>DEERE</b>					
<b>KUBOTA</b>	<b>A-70260704</b>	Shaft, PTO (540/1000 RPM) NOTE: Center mounting ring is 5.750" dia., w/ 6 bolt holes inner & outer.	8.00 Lbs.		
		<b>Dim/Info:</b> 7.875" Long			
	<b>For Models:</b> (175, 180, 185, 7000 ALL w/ Shuttle Clutch)				
<b>LANDINI</b>					
<b>LEYLAND</b>					
<b>LONG</b>	<b>A-7222286</b>	Shaft, PTO (540 RPM)	2.86 Lbs.		
		<b>Dim/Info:</b> 1.375" Shaft Dia. 6 Spline 4.890" Long			
	<b>For Models:</b> 5670, 5680, 6670, 6680, 6690, 7600, 7650, 8610, 8630				
<b>MCCORMICK</b>					
<b>OTHER</b>					
<b>RENAULT</b>	<b>A-7222287</b>	Shaft, PTO (540 RPM)	3.64 Lbs.		
		<b>Dim/Info:</b> 1.750" Shaft Dia. 6 Spline 4.890" Long			
	<b>For Models:</b> 5670, 5680, 6670, 6680, 6690, 7600, 7650, 8610, 8630				
<b>SAME</b>					
<b>VALTRA</b>					
<b>VERSATILE</b>	<b>A-72221857</b>	Shaft, PTO (1000 RPM)	2.98 Lbs.		
		<b>Dim/Info:</b> 21 Spline 4.780" Long			
	<b>For Models:</b> 5670, 5680, 6670, 6680, 6690, 7600, 7650, 8610, 8630				
<b>YANMAR</b>					
<b>ZETOR</b>					
<b>SCHWARTZ</b>					
<b>SPEECO</b>					
	<b>A-72094490</b>	Shaft, PTO (540 RPM) <b>Replaces:</b> 72092111	3.40 Lbs.		
		<b>Dim/Info:</b> 6 Spline 5.125" Long			
	<b>For Models:</b> 6080				
	<b>A-5149242</b>	Shaft, PTO (1000 RPM) <b>Replaces:</b> 72092112	3.40 Lbs.		
		<b>Dim/Info:</b> 21 Spline 4.350" Long			
	<b>For Models:</b> 6080				
	<b>A-70266975</b>	Shaft, PTO (540/1000 RPM) NOTE: Center mounting ring is 5.750" dia., w/ 6 bolt holes inner & outer.	7.89 Lbs.		
		<b>Dim/Info:</b> 8.625" Long			
	<b>For Models:</b> 7010, 7020, 7030, 7040, 7045, 7050, 7060, 8010, 8030, 8050				
	<b>A-70269141</b>	Shaft, PTO (1000 RPM)	7.58 Lbs.		
		<b>Dim/Info:</b> 27 Spline 11.540" Long			
	<b>For Models:</b> 7010, 7020, 7030, 7040, 7045, 7050, 7060, 8010, 8030, 8050				
	<b>A-2387724</b>	Shaft, PTO (1000 RPM)	6.80 Lbs.		
		<b>Dim/Info:</b> 21 / 20 11.540"			
	<b>For Models:</b> 7085, 7110				
	<b>A-4337923</b>	Shaft, PTO (540 RPM) <b>Replaces:</b> 2387727	6.67 Lbs.		
		<b>Dim/Info:</b> 20 / 6 11.540"			
	<b>For Models:</b> 7085 2WD SN<7434/3000 4WD SN <7435/2000, 7110 SN <7438/3000				
	<b>A-4335573</b>	Shaft, PTO (540/1000 RPM)	8.56 Lbs.		
		<b>Dim/Info:</b> 21 / 20 / 6 11.170"			
	<b>For Models:</b> 7145				
	<b>A-72161416</b>	Hub, PTO Drive	4.55 Lbs.		
		<b>Dim/Info:</b> 17 Spline 6.375" Dia.			
	<b>For Models:</b> 9130, 9150				
	<b>A-70235823</b>	Hitch, Lift Rod	4.34 Lbs.		
					
	<b>A-70234884</b>	Lift rod trunnion	1.26 Lbs.		
					
	<b>A-70235820</b>	Lower yoke clevis	4.02 Lbs.		
					
	<b>For Models:</b> D10, D12, D15				

\*\*\* Truck icon indicates the item is shipped via truck freight. \*\*\*

# Rockshaft/Hitch/PTO/Drawbar

**A-70254111** Screw, Lift Link 3.40 Lbs.



**Dim/Info:**  
12.875" Long  
1.200" Dia.  
1.125-7 Thread  
6.500" Long

**For Models:** 190, 190XT, 200

**A-70254112** Screw, Lift Link 3.64 Lbs.



**Dim/Info:**  
13.625" Long  
1.200" Dia.  
1.125-7 Thread  
5.750" Long

**For Models:** D17, 170, 180, 185 SN <-5707


**A-70257039** Screw, Lift Link 3.62 Lbs.



**Dim/Info:**  
13.750" Long  
1.200" Dia.  
1.125-7 Thread  
6.125" Long

**For Models:** 175 SN <-6862, 7000 SN <-8959, 200 SN 4001->, 185 SN 5707-14290

**A-70257726** Clevis, Lift Link 3.60 Lbs.



**For Models:** D17, 170, 175, 180, 185, 190, 190XT

**A-70242319** Sway Block (LH) (Cat. II) 8.48 Lbs.



**For Models:** 170, 175, 180, 185

**A-70242320** Sway Block (RH) (Cat. II) 8.38 Lbs.



**For Models:** 170, 175, 180, 185

**A-70239813** Drawbar 45.02 Lbs.  
(3) Holes @ 1.720", 4.331" & 8.332" From Front.



**Dim/Info:**  
52.250" Long  
2.500" Wide  
1.250" High

**For Models:** D19, 190, 190XT, 7000, 200

**A-70255779** Drawbar 46.80 Lbs.  
(3) Holes @ 1.720", 4.331", 5.692" & 8.332" From Front.



**Dim/Info:**  
54.250" Long  
2.500" Wide  
1.250" High

**For Models:** 7000

**A-702725045** Drawbar 83.00 Lbs.  
(3) 1.313" Dia. Front Holes @ 2.000", 4.000", & 15.000" From Front  
**Replaces:** 2725045, 2692234, 2658105



**Dim/Info:**  
62.875" Long  
3.000" Wide  
1.625" High

**A-70265823** Pin, Front Drawbar 1.13 Lbs.



**For Models:** 7010, 7020, 7030, 7040, 7045, 7050, 7060, 8010, 8030, 8050

**A-70254452** Drawbar (Standard) 43.70 Lbs.



**Dim/Info:**  
2.500" Wide  
1.250" Thick  
50.500" Long

**For Models:** 170, 175, 180, 185, D17 SERIES IV

**A-70255778** Drawbar, Wide Swing 45.90 Lbs.



**Dim/Info:**  
2.500" Wide  
1.250" Thick  
54.000" Long

**For Models:** 170, 175, (180, 185 ALL W/ 2 SPEED PTO)

**A-4334458** Drawbar, Small Swing 64.46 Lbs.  
(3) 1.312" dia. holes @ 1.410", 3.178", & 6.340" from front.



**Dim/Info:**  
52.750"  
3.150"  
1.500"

**For Models:** 7085, 7110, 7120

**A-70263647** Drawbar 25.90 Lbs.



**Dim/Info:**  
35.870" Long  
1" Thick  
2.750" Wide

**A-72092316** Pin, drawbar front 1.24 Lbs.



**For Models:** 6060, 6070 SN <1188, 6080 SN <6500

**A-72094177** Drawbar 39.18 Lbs.




**Dim/Info:**  
35.870" Long  
1.687" Thick  
2.750" Wide

**A-72094029** Pin, Drawbar Front 1.38 Lbs.




**For Models:** 6070 SN 1188>, 6080 SN 6500>

**A-49A301** Hitch, 3-PT 180.52 Lbs.



**For Models:** WD, WD45

**A-49A302** Hitch, 3-PT 175.00 Lbs.  
Cat. I/II (Use original swinging drawbar)



**For Models:** D14, D15

**A-72093884** Arm, Pull 25.60 Lbs.



**For Models:** 5045

- AGCO
- ALLIS CHALMERS
- DEUTZ
- MASSEY FERGUSON
- WHITE/OLIVER
- CNH
- CASE-IH
- FORD / NEW HOLLAND
- FIAT
- BELARUS
- BOBCAT
- JCB
- JOHN DEERE
- KUBOTA
- LANDINI
- LEYLAND
- LONG
- MCCORMICK
- OTHER
- RENAULT
- SAME
- VALTRA
- VERSATILE
- YANMAR
- ZETOR

SCHWARTZ  
SPEECO

\*\*\* Truck icon indicates the item is shipped via truck freight. \*\*\*